

SPECIFICATIONS – 175HP FOUR STROKE

HP / Kw	175 / 130
Engine type	V-6
MidSection	Conventional MidSection
Displacement (CID/CC)	209 CID
Displacement (L)	3.4L
Cylinder Configuration	V-6 [64 degree] with Dual Overhead Cam [DOHC] and 24-valves
Full throttle RPM	5000-5800
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian

Compatible with SmartCraft digital technology	Yes
Starting	Electric Start with SmartStart Protection
Controls	Remote Mechanical or Digital Throttle & Shift (DTS)
Steering	Big Tiller (optional) Hydraulic (standard) Power (optional)
Shaft length	20" / 508 mm 25" / 635 mm
Gearcase ratio	1.85:1
Dry weight *Lightest model available	475 lbs / 216 kgs
CARB star rating	3
Bore and stroke	3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	SmartCraft PCM 112 Digital Inductive
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R

Gearcase options	4.8"
Trim system	Power trim and tilt
Exhaust system	Through prop
Color	Phantom Black
Lubrication system	Integrated wet sump
Oil Capacity	7.0 Quarts / 6.6 Liters
Maximum Trim Range	20° (-6° to 14°)
Maximum Tilt Range	73° (-6° to 67°)

[\[BACK TO MOTORS\]](#)