

ENGINE DETAILS 225 PRO XS

More power. Less fuel consumed. Fewer emissions. Great for bass and multi-species fishing boats.

SPECIFICATIONS – 225

HP / kW	225 / 168
Engine type	V-8
MidSection	Conventional MidSection
Displacement (CID/CC)	279 CID
Displacement (L)	4.6L
Cylinder Configuration	V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM	5600-6200
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Electric Start with SmartStart Protection
Controls	Remote Mechanical or Digital Throttle & Shift (DTS)
Steering	Big Tiller (optional) Hydraulic (standard) Power (optional)
Shaft length	20" / 508 mm 25" / 635 mm
Gearcase ratio	1.75:1
Dry weight *Lightest model available	505 lbs / 229 kgs
CARB star rating	3
Bore and stroke	3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	SmartCraft PCM 112 Digital Inductive

Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	20": TorqueMaster 25": 5.44"
Trim system	Power trim and tilt
Exhaust system	Through prop
Color	Phantom Black
Lubrication system	Integrated wet sump
Oil Capacity	7.0 Quarts / 6.6 Liters
Maximum Trim Range	20° (-6° to 14°)
Maximum Tilt Range	73° (-6° to 67°)

[\[BACK TO MOTORS\]](#)