

SPECIFICATIONS – 300 VERADO

HP / kW	300 / 224
Engine type	V-8
MidSection	Advanced MidSection (AMS)
Displacement (CID/CC)	279 CID
Displacement (L)	4.6L
Cylinder Configuration	V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM	5200-6000
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	115-amp (1449 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian

Compatible with SmartCraft digital technology	Yes
Starting	Electric Start with SmartStart Protection
Controls	Digital Throttle & Shift (DTS)
Steering	Electro-hydraulic power steering Joystick Piloting for Outboards
Shaft length	20" / 508 mm 25" / 635 mm 30" / 762 mm
Gearcase ratio	1.75:1 or 1.85:1
Dry weight *Lightest model available	600 lbs / 272 kgs
CARB star rating	3
Bore and stroke	3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	SmartCraft PCM 112 Digital Inductive
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R

Gearcase options	5.44"
Trim system	Power trim and tilt
Exhaust system	Through prop
Counter Rotation	Available
Color	Cold Fusion White Pearl Fusion White Phantom Black Warm Fusion White
Lubrication system	Integrated wet sump
Oil Capacity	7.0 Quarts / 6.6 Liters
Maximum Trim Range	20° (-6° to 14°)
Maximum Tilt Range	73° (-6° to 67°)

[\[BACK TO MOTORS\]](#)