

SPECIFICATIONS – 350 VERADO

HP / Kw	350 / 257
Engine type	Inline 6
Displacement (L)	2.6
Full throttle RPM	5800-6400
Air induction	Supercharged with charge air cooling and electronic boost pressure control
Fuel induction system	Sequential multi-port electronic fuel injection (EFI)
Alternator amp / Watt	70 amp / 882 watt (Belt-Driven)
Recommended fuel	Unleaded Regular 89 Octane Minimum (R+M)/2 or 93 RON Unleaded 91 Octane or 95 RON for premium performance in all conditions 10% Ethanol Maximum
Recommended oil	Mercury FourStroke 25W40 Marine Oil
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes

Starting	Smart Start Electric
Controls	SmartCraft Digital
Steering	Electro-hydraulic power steering
Shaft length	20" / 508 mm 25" / 635 mm 30" / 762 mm
Gearcase ratio	1.75:1
Dry weight *Lightest model available	668 lbs / 303 kg
CARB star rating	2
Gearcase options	5.44"
Trim system	Power trim and tilt with SmartCraft programmable tilt
Counter Rotation	Available
Color	Cold Fusion White Pearl Fusion White Phantom Black Warm Fusion White

[\[BACK TO MOTORS\]](#)